GRASSIpietre s.r.l.
Lavorazione di pietre naturali dal 1880. Cave proprie.
Via Madonetta, 2 ph. +39 0444 639092 info@grassipietre.it REA 291917/VI
36024 Nanto (VI) Italy fax +39 0444 730071 www.grassipietre.it P.I. 03013000249

Instructions for Vicenza stone water- and oil-repellent treatment (for interior application)

Preliminary information:
Water- and oil-repellent products should be applied with a brush or roller in several layers (preferably 4 applications), at an interval of some hours from one application to the next (according to temperature and weather conditions). All the mentioned products are ready for use and do not need to be diluted. They should be applied on dry, clean stone (any residual traces of grout or dust must preventively be removed with thin sandpaper or with an abrasive tampon).
It is possible to walk on the treated elements 24-48 hours after application, according to the room temperature.

Contract specification:
Stone laying and treatment consists in the supply and application of a certain number of layers (3-4) of water- and oil- repellent products, after dry-cleaning with abrasive net brush (wood polisher) and either tampon or thin sandpaper as far as walls are concerned.

Recommended products and application phases:

1. first application of 2 layers of “W68” by FILA (water-based stain-resistant organic resin protection, which does not alter the stone surface). Average performance: 10 m^2/litre.

2. next application of 2 layers of “FILA JET” by FILA, which protects the treated stone from dirt, giving it a velvety aspect. Average performance: 15 m^2/litre for each layer (the various applications should be performed at an interval of some hours, in order to allow the product to dry).

3. As far as the first maintenance treatment is concerned, the application of a layer of “FILA JET” by FILA is recommended 6 months after the first treatment. The product should not be diluted and it should be applied on a clean surface without rinsing.

4. As far as the second maintenance treatment is concerned, the application of a layer of “FILA CLASSIC” by FILA is recommended 1 year after the first treatment. The product must be applied with the wash-wax technique, with 3 glasses of product diluted in a water bucket and without rinsing.

5. “FILA CLEANER”, diluted in water or used pure on stained spots, is suitable for daily cleaning.

For further information, please see the product technical specifications or contact our technical office.